AAH

HIRE | 24HRS | 7DAYS

Helping your business reach new heights safely





HIRE | 24HRS | 7DAYS

Helping your business reach new heights safely

VERTICAL ELECTRIC LIFTS: All models have electric motors with non-marking tyres and fitted with extension decks.

AAH MODEL	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	STOWED HEIGHT (M)	KG LIFT CAPACITY (KG)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	GROSS WEIGHT (KG)	PLATFORM SIZE (M)
TM12	3.66	5.66	1.64	227	0.76	1.36	776	0.74 x 0.89
GR15	4.47	6.47	1.57	277	0.75	1.35	990	0.74 x 0.89
SJ16	4.75	6.75	1.79	227	0.77	1.37	971	0.69 x 0.85
GR20	6.07	8.07	1.98	159	0.80	1.35	1,112	0.75 x 0.89
AWP30	8.80	10.80	1.98	159	0.74	1.35	352	0.69 x 0.66
STAR 10	8.00	10.00	1.99	200	1.00	2.70	2,735	0.78 x 0.99

SCISSOR ELECTRIC LIFTS: All models have solid non-marking tyres and fitted with extension decks.

AAH MODEL	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	STOWED HEIGHT (M)	KG LIFT CAPACITY (KG)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	GROSS WEIGHT (KG)	PLATFORM SIZE (M)
1330	3.80	5.80	1.80	227	0.76	1.46	900	0.61 x 1.26
19	5.80	7.60	2.00	227	0.81	1.83	1,498	0.74 x 1.60
26N	7.92	9.92	2.26	227	0.82	2.44	1,956	0.79 x 2.40
26	7.92	9.92	2.26	454	1.17	2.44	2,447	1.16 x 2.40
32N	9.75	11.75	2.43	227	0.81	2.44	2,352	0.79 x 2.40
32	9.75	11.75	2.40	318	1.17	2.44	2,812	1.16 x 2.40
4045	11.8	13.80	2.50	350	1.20	2.74	3,175	1.20 x 2.30
40LE	12.19	14.00	2.81	360	1.73	3.10	4,863	1.65 x 3.83
4655ES	13.95	15.95	2.77	350	1.41	3.11	3,701	2.84 x 1.35

N = Narrow Deck Scissor Lift

SCISSOR LIFTS: Diesel scissor lifts have (puncture proof) foam filled tyres and extension decks (*dual extension decks).

AAH MODEL	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	STOWED HEIGHT (M)	KG LIFT CAPACITY (KG)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	GROSS WEIGHT (KG)	PLATFORM SIZE (M)
26	7.90	9.80	2.40	567	1.77	3.37	3,469	1.50 x 4.00
32	9.75	11.58	2.50	454	1.77	3.37	4,153	1.50 x 4.00
3390*	10.06	12.06	2.71	1,134	2.34	3.89	5,433	1.83 x 3.98
4069RT	12.30	14.30	2.74	363	1.75	3.12	5,074	1.60 x 4.32
43*	13.10	14.90	2.93	680	2.29	4.88	7,209	1.83 x 6.57
53*	16.20	18.00	3.15	680	2.29	4.88	7,733	1.83 x 6.57

All specifications shown above are approximate only and are subject to manufacturers change without notice.

SCISSOR LIFTS: Specialised

AAH MODEL	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	STOWED HEIGHT (M)	KG LIFT CAPACITY (KG)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	GROSS WEIGHT (KG)	PLATFORM SIZE (M)
ATHENA 850	5.90	7.90	2.80	250	1.30	1.94	2,160	1.50 x 0.78
ATHENA 1090	8.00	10.00	2.94	300	1.64	2.29	2,900	1.80 x 1.30
30 SPEED LEVEL	9.00	11.00	2.67	680	2.10	4.27	3,892	4.27 x 1.82

KNUCKLE BOOMS: Electric

AAH MODEL	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	STOWED HEIGHT (M)	OVERALL WIDTH (M)	JIB ROTATION	OVERALL LENGTH (M)	HORIZONTAL REACH (M)	UP & OVER HEIGHT (M)	KG LIFT CAPACITY	PLATFORM SIZE (M)	GROSS WEIGHT (KG)
30	8.89	10.89	2.00	1.19	YES	5.31	6.25	3.86	227	0.76 x 1.22	6,450
34	10.50	12.30	2.00	1.47	NO	5.72	6.80	4.60	227	0.76 x 1.42	5,216
40	12.20	14.00	1.97	1.50	YES	6.70	6.91	6.55	227	0.76 x 1.22	6,972
45	13.92	15.92	2.00	1.80	NO	6.50	7.65	6.73	227	0.76 x 1.22	7,620
M600	18.39	20.39	2.54	2.42	NO	10.15	13.54	N/A	230	0.76 x 1.83	7,702

KNUCKLE BOOMS: Diesel

AAH MODEL	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	STOWED HEIGHT (M)	OVERALL WIDTH (M)	JIB ROTATION	OVERALL LENGTH (M)	HORIZONTAL REACH (M)	UP & OVER HEIGHT (M)	KG LIFT CAPACITY	PLATFORM SIZE (M)	GROSS WEIGHT (KG)
34	10.60	12.40	2.00	1.85	N/A	5.70	6.80	4.60	227	0.76 x 1.42	5,090
45	14.07	16.07	2.11	2.29	N/A	6.53	7.47	7.67	227	0.76 x 1.83	6,577
51	15.62	17.62	2.69	2.29	N/A	7.50	9.25	7.16	227	0.70 x 1.83	7,213
60	18.29	20.39	2.50	2.46	N/A	8.15	11.50	8.23	227	0.90 x 2.44	10,215
80	23.77	25.77	3.00	2.49	N/A	11.27	18.29	8.83	227	0.91 x 2.44	17,000
135	41.15	43.15	3.07	2.46	3.94	12.93	21.26	23.01	227 - 450	0.91 x 2.44	20,336

SPECIALISED KNUCKLE BOOMS: Hybrid

AAH MODEL	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	STOWED HEIGHT (M)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	HORIZONTAL REACH (M)	UP & OVER HEIGHT (M)	KG LIFT CAPACITY	PLATFORM SIZE (M)	GROSS WEIGHT (KG)
HYBRID 340AJ	10.30	12.30	2.00	1.93	5.52	6.06	5.17	230	1.52 x 0.76	4,675
HR12	10.20	12.20	1.95	1.60	4.10	6.10	4.00	200	1.10 x 0.65	3,470
HR17	15.20	17.20	2.10	2.00	6.35	9.40	7.00	225	1.80 x 0.85	5,000
HR21	18.80	20.80	2.18	2.27	6.62	13.00	7.00	250	1.80 x 0.80	6,680
Z60FE	18.10	20.10	2.54	2.49	8.15	11.15	7.39	227	2.44 X 0.91	7,756

All specifications shown above are approximate only and are subject to manufacturers change without notice.

BOOM LIFTS: Straight Diesel. All boom lifts are fitted with 240V generators and jibs.

AAH MODEL	PLATFORM HEIGHT (M)	WORKING HEIGHT (M)	STOWED HEIGHT (M)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	HORIZONTAL REACH (M)	KG LIFT CAPACITY	HC CAPACITY (KG)	PLATFORM SIZE (M)	GROSS WEIGHT (KG)
45	13.70	15.50	2.49	2.30	8.48	11.20	227	300 / 454	0.91 x 2.44	7,116
65	19.80	21.80	2.72	2.49	9.50	17.10	227	300 / 454	0.76 x 2.44	10,102
85	25.90	27.90	2.80	2.44	12.40	23.40	227	300 / 454	0.91 x 2.44	16,266
135	41.15	43.15	3.05	2.49	11.86	24.38	227	300 / 454	0.91 x 2.44	20,411
180	54.86	56.86	3.05	2.49	14.33	24.38	340	300 / 454	0.91 x 2.44	24,948

TELEHANDLERS

AAH MODEL	MAX LIFT CAPACITY (KG)	MAX LIFTING HEIGHT	LIFT CAPACITY AT MAX HEIGHT	HORIZONTAL REACH (M)	LIFT CAPACITY AT MAX REACH (KG)	STOWED HEIGHT (M)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	WEIGHT (KG)
25.6	2500	5.78	1700	3.35	800	1.95	1.85	4.12	5,100
30.9	3000	8.70	2500	5.70	800	2.22	2.00	4.77	6,250
35.10	3500	9.75	2000	6.55	400	2.31	2.29	4.95	8,000
40.13	4000	12.40	2000	8.80	750	2.46	2.32	5.59	10,420
40.17	4000	16.60	3800	9.64	500	2.55	2.36	6.27	12,260
70.10	7000	9.50	4300	5.45	2000	2.49	2.38	5.91	12,100

FORKLIFTS

AAH MODEL	MAX LIFT CAPACITY (KG)	LOAD CENTRE	MAX WORKING HEIGHT (M)	STOWED HEIGHT (M)	OVERALL WIDTH (M)	OVERALL LENGTH (M)	WEIGHT (KG)
2.5T	2500	500mm	3.00	1.99	1.15	2.61	3,440
3.0T	3000	500mm	4.145	2.050	1.225	2.73	4,350
BUGGY	2500	500mm	3.30	1.95	1.45	2.98	4,260

All specifications shown above are approximate only and are subject to manufacturers change without notice.



Introduction to AAH

AAH commenced operation in 2006 and is a leader in the Australian Access Equipment Rental Industry.

We are passionate about being a specialist provider of Elevated Work Platforms with a branch network positioned to cover the east and west coast of Australia.

AAH OFFERS

SAFETY

- Safety is an integral part of everything we do. AAH is committed to continuously improving and implementing safety across all areas of our business.
- Company-wide culture and rigorous enforceable safety procedures and KPI's.
- Our team are proactive in implementing and delivering safe work initiatives.

RELIABILITY

- Regular scheduled and preventive maintenance performed on all equipment in line with industry requirements.
- Exceeds manufacturer's requirements and ensures our fleet is the most reliable in the industry.
- Factory skilled service technicians maintain our fleet to the highest standards and are ready to respond to any equipment failures, minimising downtime and increasing efficiency.

AVAILABILITY

- We are available when you need us most - with a team of customer service support employees.
- We respond to your equipment and service needs 24/7, 365 days a year.
- Our commitment is that you are answered by a person no matter what time of day or night.

Free Call 133 224
www.aah.com.au



HIRE | 24HRS | 7DAYS



JLG Genie DIECI

NEW SOUTH WALES

Sydney Branch

1/5 Melito Court,
Prestons
NSW 2170

VICTORIA

Melbourne Branch

169 Studley Court,
Derrimut
VIC 3026

WESTERN AUSTRALIA

Perth Branch

32 Allott Way,
Maddington
WA 6109

QUEENSLAND

Brisbane Branch

T2, 1-7 Australand Drive,
Berrinba
QLD 4117

Free Call 133 224

www.aah.com.au